

# इंटरनेट

# मानक

## Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 3741-2 (1990): Medical Glass Instruments - Sedimentation Tubes, Part 2: Wintrobe Tube [MHD 12: Hospital Equipment]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



*Indian Standard*

**MEDICAL GLASS INSTRUMENTS —  
SEDIMENTATION TUBES — SPECIFICATION**

**PART 2 WINTROBE TUBE**

*( Second Revision )*

भारतीय मानक

चिकित्सीय कांच उपकरण — अवक्षेपण ट्यूबें — विशिष्टि

भाग 2 विंट्रोब ट्यूब

( दूसरा पुनरीक्षण )

UDC 616·151·6-008·816 : 542·231·231·3 : 666·172·7

© BIS 1990

**BUREAU OF INDIAN STANDARDS**  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI 110002

## FOREWORD

This Indian Standard (Second Revision) was adopted by the Bureau of Indian Standards on 20 March 1990, after the draft finalized by the Medical Instruments and Disposables Sectional Committee had been approved by the Medical Equipment & Hospital Planning Division Council.

This Indian Standard was first published in 1966 and revised in 1980. In this second revision, the standard has been splitted in two parts:

Part 1 Westergren tube

Part 2 Wintrobe tube

This Part 2 deals with wintrobe tubes used to determine the erythrocyte sedimentation rate (ESR) in human blood containing an anti-coagulant by macro method. In this revision, modifications have been incorporated in the requirements of material, workmanship and finish, and scale graduations.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***MEDICAL GLASS INSTRUMENTS—  
SEDIMENTATION TUBES—SPECIFICATION****PART 2 WINTROBE TUBE***( Second Revision )***1 SCOPE**

**1.1** This standard specifies requirements for Wintrobe tubes used to determine the sedimentation rate of erythrocytes in human blood containing an anti-coagulant by macro method.

**2 MATERIAL**

**2.1** The Wintrobe tube shall be made from transparent glass (other than soda glass) tubing, free from visible defects and reasonably free from internal stress. The glass shall pass alkalinity test prescribed in IS 2303 : 1963 'Methods of grading glass for alkalinity'. It may also be made from functionally compatible transparent plastics suitable for process to be used for sterilization and free from defects liable to make it unfit for correct use.

**3 SHAPE AND DIMENSIONS**

**3.1** The shape and dimensions of Wintrobe tubes shall be as shown in Fig. 1.

**4 WORKMANSHIP AND FINISH**

**4.1** The Wintrobe tubes shall be well annealed, free from bubbles and as free as possible from striae, stones and other visible defects. The top of the tube shall be slightly rounded. It shall be ground smooth and square with the axis of the tube.

**4.2** The lower end of the tube shall be closed with internally flat bottom.

**4.3** The specified bore of the tube shall be maintained throughout the length.

**5 SCALE GRADUATION AND  
NUMBERING****5.1 Scale**

**5.1.1** The Wintrobe tubes shall be provided

with a scale of 100 mm length graduated in mm starting from the base of the lumen of the tube.

**5.1.2** The scale shall be numbered from 0 to 90 downward and from 10 to 100 upward, the two numberings being on either side of the scale shown in Fig. 1.

**5.1.3** The graduation lines and numbering shall be clear, easy to distinguish, permanent and of uniform size. The graduation lines shall be of uniform thickness not exceeding 0.3 mm.

**5.1.4** The numbering of the graduation lines and their lengths shall be as follows:

*Long Graduation Lines*—0 mm, 10 mm, 20 mm, etc. The length of lines to be at least 6 mm.

*Medium Graduation Lines*—5 mm, 15 mm, 25 mm, etc. The length of lines to be at least 4 mm.

*Short Graduation Lines*—The length of lines to be at least 2.5 mm.

The numbering shall be close to but shall not touch its corresponding lines.


**6 MARKING**

**6.1** Each Wintrobe tube shall be legibly and indelibly marked with the following information:

- a) Indication of the source of manufacture, and
- b) Unit 'mm' placed close to the top most numbering.

**7 PACKING**

**7.1** The Wintrobe tubes shall be packed as required by the user.



All dimensions in millimetres.

FIG. 1 WINTROBE TUBE

### **Standard Mark**

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.



## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc : No MHD 12 (2106)

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002  
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha  
(Common to all Offices)

### Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 31 331 13 75
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola CALCUTTA 700054	37 86 62
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18 43
Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113	41 29 16
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	6 32 92 95

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.  
COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI.  
HYDERABAD. JAIPUR. KANPUR. PATNA. THIRUVANANTHAPURAM.